



The Westport Steel Gas Stove is an affordable solution for a midsize to large living space. It offers the performance of the original Westport Cast Iron Gas Stove with a more modern design and steel outer construction. It's available in both Nova or IPI and can be vented top or rear, and is also compatible with a B vent.

Design Features

- Remote thermostat compatible
- Steel construction
- Ceramic log set
- Quick release glass door system
- Top vent / rear vent / B vent
- ClearView Safety Screen
- Optional 150 CFM fan
- Nova and IPI editions

Stove Specifications

| BTU Maximum Input - NG | 30,000 BTU | | | | |
|------------------------|--------------------------------------|-----------------------|-----------------------|--|--|
| Turn Down* | up to 50% | | | | |
| Heating Area | | 1,700 ft ² | | | |
| P4 Efficiency | 64.9% | | | | |
| Viewing Area | 131⁄2" x 191⁄4", 260 in ² | | | | |
| Glass Size | 16½" x 20¾", 336 in² | | | | |
| Stove Dimensions | HEIGHT 27½″ | WIDTH 26¼" | DEPTH 19½ ″ | | |
| | | | | | |







High definition log set



Easy access controls



As our entry level gas stove, the S20 is the perfect solution for a smaller to mid-size living room. Its modern design blends well with a variety of décor, and its small footprint offers greater versatility in placement. It's available in IPI and can be vented top or rear.

Design Features

- Field conversion kit NG to LP
- Thermostat or remote compatible
- Ceramic log set
- Charcoal fluted liner
- Top vent / rear vent convertible
- Heavy duty heat exchangerEasy access controls
- 150 CFM variable speed fan
- ClearView Safety Screen
- IPI Valve

Stove Specifications

| BTU Maximum Input - NG | 20,000 BTU | | | | |
|------------------------|----------------|-----------------------|---------------|--|--|
| Turn Down* | up to 33% | | | | |
| Heating Area | | 1,100 ft ² | | | |
| P4 Efficiency 74.5% | | | | | |
| Viewing Area | 16½″ | x 18¾″, 3 | 09 in² | | |
| Glass Size | 19¾″ | x 17½″, 3 | 46 in² | | |
| Stove Dimensions | HEIGHT 33½″ | WIDTH 24½″ | DEPTH 18¾″ | | |







Steel fireplace grate





Modern steel construction







Cube Gas Stove with Removable Safety Screen

The modern design of the Cube Gas Stove can be customized with either a standard table or a long table for a more creative install. Powder coated exterior panels are also available in three additional colors.

Options

Exterior Panels:

- Painted Metallic Black (Standard)
- Powder Coated Sage Green
- Powder Coated Bordeaux Red
- Powder Coated Cypress Green

Physical Options: - Table

- Long Table (Left & Right Compatible)

Design Features

- Thermostat Compatible
- Top Vent / Rear Vent Convertible
- IPI Valve
- Durable Stainless Steel Burner
- Modern Design
- Ceramic Fluted Liner
- High Definition Log Set
- Full Ceramic Glass Panel
- Optional 150 cfm Fan Kit
- Removable Safety Screen

Stove Specifications

| BTU Maximum Input - NG | 30,000 BTU | | | |
|------------------------|--------------------------|-----------------------|------------------|--|
| Turn Down | | 33% | | |
| Heating Area | | 1,700 ft ² | | |
| P4 Efficiency | | 60% | | |
| Viewing Area | 135⁄8″ x 187⁄8″, 254 in² | | | |
| Dims w/Table | HEIGHT 35" | WIDTH 24" | DEPTH 17 7/8" | |
| Dims w/Long Table | 35" | 44" | 19¼" | |













Introducing the Enviro S50, the most elegant addition to our freestanding lineup. This sleek and modern design sports 180° of curved glass to show off its ultra high definition log set. Capable of both rear and top venting. The S50 also has multiple color and pedestal options to choose from.

Design Features

- Top vent / rear vent convertible
- Optional field conversion kit NG to LP
- Optional 70 CFM Circulation Fan available
- Optional Powder Coated Doors
- Optional Suspended Installation Kit

Options

- Color Options: - Painted Metallic Black
- Powder Coated Carrara White
- Media Options: - Traditional or Birch Log Set - River Rock & Twig Set - Glass Media
- Liner Options: - Steel Painted Liner (Included) - Black Glass Liner - Fluted Liner
- Physical Options: - Pole Pedestal - Wood Pedestal
- Suspended Installation Kit

BTU Maximum Input - NG 30,000 BTU Turn Down 33% Heating Area 1,500 ft² P4 Efficiency 68% Viewing Area H/W (Flat-on) 15" x 18", 270 in² Glass Size H/W

Stove Specifications



† Height includes a pedestal.





Radiant Red Door Glass Media Black Glass Liner

6

The S50 CURVED GAS STOVE

S50 with Pole Pedestal - Carrara White, Birch Log Set, Black Glass Liner



Sage Green Door Traditional Log Set Steel Painted Liner

Add a touch of

Optional powder coated doors are available in these three colors to help you create an S50 gas stove that's uniquely yours.





The Westley's European cast iron outer construction creates a traditional aesthetic with modern accents. What really sets the Westley apart is its 180° viewing angle giving plenty of exposure to the high definition log set and stainless steel burner. The Westley is available in both a matte black finish or an antique bronze.

Design Features

- European made castings
- 180° viewing angle
- Heavy duty heat exchanger
- B-vent compatible (IPI)
- 130 CFM variable speed fan
- ClearView Safety Screen
- Ultra HD log set
- True to life flame presentation
- Multiple Finishes:
 Painted Black
 Antique Bronze

Stove Specifications

| BTU Maximum Input - NG 29,000 BTU | | | | |
|-----------------------------------|-----------------------|---------------|------------------|--|
| Turn Down 33% | | | | |
| Heating Area | 1,500 ft ² | | | |
| P4 Efficiency | 67% | | | |
| Combined Viewing Area | 418 in ² | | | |
| Glass Size | 525 in ² | | | |
| Stove Dimensions | HEIGHT 27½″ | WIDTH 26¾″ | DEPTH 199/16″ | |





8 Piece ultra high definition log set

8

European castings - Painted Black



Flame visible from three sides





The Westport Cast Iron is one of our most popular freestanding gas stoves. Its traditional design and cast iron outer construction provide a classy appearance. The Westport Cast Iron Gas Stove is available in a painted black matte finish or an antique chestnut porcelain enameled finish. It can be vented top, rear, and is also compatible with a B vent.

Design Features

- Remote thermostat compatible
- Cast iron outer construction
- Ceramic log set
- Quick release glass door system
- Top vent / rear vent / B ventSafety screen
- Optional 150 CFM fan
- Nova and IPI editions
- Nova and in reditions
- Multiple Finishes:
 Painted Black
 Enameled Antique Chestnut

Stove Specifications

| BTU Maximum Input - NG | 3 | 0,000 BT | U |
|------------------------|--|---------------|-----------------------|
| Turn Down* up to 50% | | | |
| Heating Area | 1,700 ft ² 64.9% 13½″ x 19¼″, 260 in ² 16½″ x 20¾″, 336 in ² | | |
| P4 Efficiency | | | |
| Viewing Area | | | |
| Glass Size | | | |
| Stove Dimensions | HEIGHT 27½″ | WIDTH 25¾″ | DEPTH 19½ ″ |









Enameled antique chestnut finish



The S40 Freestanding Gas Stove offers a maximum BTU output of 40,000 making it excellent at heating large living spaces. It has a modern design and a 5/16" steep plate top. Instead of a typical burner tube layout, the S40 uses a ceramic log burner that blends in with the rest of the log set to create a more realistic appearance.

Design Features

- Heavy duty heat exchanger
- Thermostat or remote compatible
- Ceramic log set and burner
- 5/16" steel plate top
- Ceramic charcoal fluted liner
- 150 CFM variable speed fan
- Optional B vent adaptor
- ClearView Safety Screen
- = |P|

Stove Specifications

| BTU Maximum Input - NG | 40,000 BTU | | | |
|------------------------|---|--|--|--|
| Turn Down | up to 33% | | | |
| Heating Area | 2,000 ft ² | | | |
| P4 Efficiency 65.9% | | | | |
| Viewing Area | 15" x 19¾", 296 in² | | | |
| Glass Size | 16 ⁷ / ₈ " x 21", 355 in ² | | | |
| Stove Dimensions | HEIGHT WIDTH DEPTH 285%" 261%" 227/16" | | | |





Modern design

Ceramic burner





Heavy duty heat exchanger



The Berkeley's European cast iron outer construction creates a traditional esthetic with modern accents. What really sets the Berkeley apart is its 180° viewing angle, providing plenty of exposure to the high definition log set and ceramic burner. The Berkeley is available in both a matte black finish and enameled antique chestnut.

Design Features

- European-made castings
- 180° viewing angle
- IPI edition
- Heavy duty heat exchanger
- Ceramic log set and burner
- 150 CFM variable speed fan
- ClearView Safety Screen
- Two Stage Burner
- Multiple Finishes:
 Painted Black
- Enameled Antique Chestnut

Stove Specifications

| BTU Maximum Input - NG | 40,000 BTU | | | |
|------------------------|--|--|--|--|
| Turn Down* | up to 67.5% | | | |
| Heating Area | 2,000 ft ² | | | |
| P4 Efficiency | 66.6% | | | |
| Combined Viewing Area | 593½ in ² | | | |
| Glass Size | 724 in ² | | | |
| Stove Dimensions | HEIGHT WIDTH DEPTH 301¼″ 295/16″ 2215/16″ | | | |



Flame visible from three sides

e sides

* Turn down is based on IPI valve with front burner being turned off. (SIT Proflame 2 models only)



9 Piece ultra high definition log set



European castings - enameled antique chestnut

Gas Stove Specifications

| Performance | S20 SMALL GAS STOVE | Westley CAST IRON GAS STOVE | Cube GAS STOVE | S50 GAS STOVE | Westport CAST IRON / STEEL STOVE | S40 Large gas stove | Berkeley CAST IRON GAS STOVE |
|--------------------------------|--|-------------------------------------|---|--|--|-------------------------------|---|
| BTU Max Input - NG | 20,000 BTU | 29,000 BTU | 30,000 BTU | 30,000 BTU | 30,000 BTU | 40,000 BTU | 40,000 BTU |
| Turn Down Nova / IPI | 33% | 33% | 33% | 33% | 50% / 33% | 33% | 67.5%* |
| Construction | Steel | Cast Iron | Steel | Steel | Cast Iron / Steel | Steel | Cast Iron |
| Nova | N/A | N/A | N/A | N/A | Available | N/A | N/A |
| IPI | Standard | Standard | Standard | Standard | Available | Standard | Standard |
| Efficiency - Steady State** | 76.2% | 68.9% | - | - | 71.3% | 70.7% | 69% |
| Efficiency FE rating † | 74.5% | 67% | 60% | 68% | 64.9% | 65.9% | 66.6% |
| Viewing Area (H/W) | 181⁄8" x 161⁄2" | 418 in ² (Front+Sides) | 135⁄8″ x 187⁄8″ | 15" x 18½" (flat-on) | 13½" x 19¼" | 15" x 19³/4" | 593 in ² (Front+Sides) |
| Actual Glass (H/W) | 19¾" x 17½" | 525 in ² (Front+Sides) | 22¼" x 20¼" | 19½″ x 29″ | 16½" x 20³/8" | 161/8″ x 21″ | 724 in ² (Front+Sides) |
| Finish | – Painted Black | – Painted Black – Antique Bronze | – Painted Black – Red or Green Outer Panel Kits | – Painted Black – PC Carrara White – White, Red or Green Door Accent Kits | – Painted Black – Enameled Antique Chestnut | – Painted Black | – Painted Black – Enameled Antique Chestnut |
| Installation | S20 Small gas stove | Westley CAST IRON GAS STOVE | Cube GAS STOVE (W/TABLE) | S50 GAS STOVE (W/PEDESTAL) | Westport CAST IRON / STEEL STOVE | S40 Large gas stove | Berkeley CAST IRON GAS STOVE |
| Dimensions | H W D 33 ¹ /2" 24 ¹ /2" 18 ³ /8" | H W D 27½″ 26¾″ 19%6″ | H W D 35" 24" 17%" | H W D 46" 20" 20" | H W D 271⁄2″ 2534″ 191⁄2″ 271⁄2″ 261⁄4″ 191⁄2″ | H W D 285%" 261/8" 227/16" | H W D |
| LP Conversion Kit (SP) | N/A | N/A | N/A | N/A | Included | N/A | N/A |
| LP Conversion Kit (IPI) | Optional | Optional | Optional | Optional | Optional | Optional | Optional |
| Venting (Direct Vent) | 4″ x 6⁵/ଃ″ | 4″ x 6⁵/8″ | 4″ x 6⁵/8″ | 4″ x 6⁵/8″ | 4″ x 6⁵/ଃ″ | 4″ x 6⁵/ଃ″ | 4″ x 6 5/8″ |
| Venting Compatibility | Top / Rear | Тор | Top / Rear | Top / Rear | Top / Rear | Тор | Тор |
| B Vent Compatibility | N/A | Yes | Yes | N/A | Yes | Yes | N/A |
| Weight | 225 lbs | 190 lbs | - | 150 lbs (Without Pedestal) | 227 lbs / 117 lbs | 275 lbs | 295 lbs |
| Convection Fan | Included | Included | Optional | Optional | Optional | Included | Included |

| Clearance to Combustibles | S20 Small gas stove | Westley CAST IRON GAS STOVE | Cube GAS STOVE | S50 GAS STOVE | Westport CAST IRON / STEEL STOVE | S40 Large gas stove | Berkeley CAST IRON GAS STOVE |
|---|-------------------------------|--------------------------------|--------------------------|-------------------------|--|-------------------------------|---------------------------------|
| Minimum distance to the stove's sides | 8" | 10 ¹ /4″ | 111⁄8″ | 12″ | 11″ | 11¾" | 12" |
| Minimum distance behind the stove | 4" | 5″ | 21⁄2″ | 3″ | 21⁄2″ | 5" | 5" |
| Minimum alcove height to top of stove | 12" | 35″ | 10″ | 16″ | 321/2″ | 285/8" | 27½" |
| Minimum distance corner to wall | 3″ | 5″ | 21⁄2″ | N/A | 21/2" | 71⁄2″ | 71⁄2″ |
| Center of vent to sidewall (at minimum corner) | 15" | 155/8″ | 24″ | 22″ | 121⁄8″ | 17¾″ | 17¾" |

* Berkeley IPI turn down based on front burner being turned off.

** Steady state rating based on conventional venting configuration.

† Based on the measured P.4-15 rating of the IPI model.

Specifications and measurements are subject to change. Please refer to owners manual for the most up to date and detailed product information.

Gas Stove Specifications

The best way to visualize your dream fireplace at home is with the Enviro App!





Manufactured by Sherwood Industries Ltd • Victoria, BC, Canada enviro.com • info@enviro.com • Printed in Canada, May 2024

